



Acoplamiento para casquillo cónico. Serie F

Shaft to Shaft Coupling. F Series

Mod. F		F40	F50	F60	F70	F80	F90	F100	F110	F120	F140	F160	F180	F200
Par Nominal [Nm] Nominal Torque		30	75	130	250	350	500	600	720	1000	2100	4300	6100	8700
Par Max [Nm] Max Torque		90	220	380	700	1000	1500	1800	2100	3000	6000	12500	16200	25000
Velocidad Max [rpm] Max Speed		4500	4500	4000	3600	3100	2800	2600	2300	2100	1800	1600	1500	1300
Diametros [mm] Diameters	A	104	133	165	187	211	235	254	279	314	359	402	470	508
	B	50	79	70	80	95	108	113	134	140	178	180	205	205
	Ø Max sin Casquillo Ø Max without Bush	30	38	45	50	60	70	80	90	100	130	140	150	150
	Ø Max Eje Shaft Ø Max	28	32	42	42	50	60	60	75	75	90	100	110	110
Tornillos Screws		4xM6	4xM6	5xM8	5xM8	6xM8	6xM10	6xM10	6xM10	6xM12	8xM12	8xM16	10xM16	12xM16
Longitudes [mm] Lengths	L	-	-	-	-	108	120	124	124	134	146	156	188	206
	N	22	25	33	24	26	29	29	25	29	33	30	46	48
	P	66	76	84	88	116	120	130	127	159	163	185	206	226
Casquillo Bush		1108	1210	1610	1610	2012	2517	2517	3020	3020	3525	4030	4535	4535