



Para motores con rotor deslizante

Applications with floating shaft

**Acoplamiento para eje directo Serie FF**

**Shaft to Shaft Coupling FF Series**

Mod. FF		1	2	3	4	5	6	7
Par Nominal [Nm] Nominal Torque		3	7	17	40	80	130	200
Par Max [Nm] Max Torque		30	75	150	300	700	1200	2000
Velocidad Max [rpm] Max Speed		3000	3000	1500	1500	1500	1500	1000
Momento de Inercia [kgm <sup>2</sup> ] Moment of Inertia		-	0.015	0.045	0.13	0.17	0.321	0.896
Ángulo de Torsión [°] Torsional Angle		4	5	6	7	8	9	10
Desplazamiento Axial [mm] Axial Misalignment		± 6	± 6	± 8	± 8	± 8	± 8	± 8
Desplazamiento Lateral [mm] Lateral Misalignment		0.7	1	1.4	1.6	1.9	2.2	2.6
Desplazamiento Angular [°] Angular Misalignment		2	2	2	2	2	2	2
Diametros [mm] Diameters	A	134	172	222	280	330	376	400
	B	34	48	65	80	80	95	110
	Ø Max Eje Shaft Ø Max	22	32	38	55	55	65	75
	Ø Pretaladrado Ø Preboring	-	-	16	18	18	18	25
Longitudes [mm] Lengths	L	65	92	117	142	178	207	233
	N	9	12	11	24	27	18	18
Masa [kg] Mass		1	3.5	7	11.5	14.5	22	35
Ref. Flector Tyre Ref.		U201	U202	U203	U204	U205	U206	U207